

SmoochSPRITZ™

Pearlized Accent Spray

- For best results, spray six to ten inches from project. For a heavier application of color, spray closer to the project.
- Before each use, shake vigorously until all particles are mixed. The sprayer can clog if particles get sucked up into the tube. Spray in direction of arrow as viewed on nozzle top.
- To speed dry time, heat with a heat tool.
- If ink dries outside the nozzle, remove the nozzle and submerge in household cleaner (such as Windex or 409), for 20 minutes. Rinse, replace the nozzle, shake well and spray.
- To eliminate overspray that can soil work areas, use with Clearsnap's Color Catcher™.
- Acid free



- Layer colors by spraying a small amount of two different colors onto your project. Start with a lighter color and end with a darker color.
- Build color by spraying several thin coats. Allow to dry between coats.
- Spray chipboard and embellish with a coordinating Smooch™ color.
- Spray a background on card and pages. When dry, stamp images.



www.clearsnap.com 1-800-448-4862





Smooch™

Pearlized Accent Ink

- Add dots of color to embellish a stamped image
- Color stamped images
- Layer color over patterned papers
- Highlight raised areas of embossed or textured papers, metal, buttons or brads
- Shake well before using

- Create a background by putting a little water into a shallow pan. Dot the surface of the water with a few drops of ink. Use more than one color. Drop a piece of cardstock onto the water's surface for a few seconds. Then lift straight up.
- Spritz a piece of cardstock with water, then wet a sponge and dot with Smooch. Use one color or more. Drag the sponge over the wet cardstock.
- Use the tip to freehand draw your own unique details and designs
- Gild the edges of papers and boxes



Clearsnap

Distinctive Inkpads and Accessories

www.clearsnap.com 1-800-448-4862